

Company name: Created by: Phone:

Date: 08/08/2022

Qty. | Description

1 SP 125-4-A



Note! Product picture may differ from actual product

Product No.: 17A243A4

Submersible borehole pump, suitable for pumping clean water. Can be installed vertically or horizontally. All steel components are made in stainless steel, EN 1.4301 (AISI 304), that ensures high corrosive resistance. This pump carries drinking water approval.

The pump is fitted with a 37 kW MMS6 motor with sand shield, water-lubricated journal bearings and a volume compensating diaphragm.

The rewindable motor contruction allows complete access to the windings for easy rewinding.

The stator windings are PE/PA insulated made for continous operations (S1).

Suitable for temperatures up to 50 °C.

The motor is fitted with a mechanical shaft seal.

The motor is for direct-on-line starting (DOL).

Liquid:

Pumped liquid: Water
Liquid max temp: 50 °C

Max liquid t at 0.5 m/sec: 50 °C

Selected liquid temperature: 20 °C

Density: 998.2 kg/m³

Technical:

Pump speed on which pump data are based: 2900 rpm

Rated flow: 125 m³/h
Rated head: 74 m
Shaft seal for motor: SIC/SIC
Approvals on nameplate: CE

Curve tolerance: ISO9906:2012 3B

Motor version: T50

Materials:

Pump: Stainless steel

EN 1.4301 AISI 304 Stainless steel

Impeller: Stainless stee

EN 1.4301 AISI 304

Motor: Cast iron

DIN W.-Nr. 0.6025 ASTM 35-40

Installation:

Pump outlet: RP6
Motor diameter: 6 inch

Electrical data:

Motor type: MMS6 Rated power - P2: 37 kW



Company name: Created by: Phone:

Date: 08/08/2022

Qty. | Description

1 Power (P2) required by pump: 37 kW Mains frequency: 50 Hz

Rated voltage: 3 x 380-400-415 V

Service factor: 1.00

 Rated current:
 87.0-84.5-85.0 A

 Starting current:
 455-495-510 %

 Cos phi - power factor:
 0.85-0.82-0.79

 Rated speed:
 2830-2860-2870 rpm

Start. method: direct-on-line

Enclosure class (IEC 34-5): IP68
Motor No: 96879428
Windings: PE2/PA

Others:

Minimum efficiency index, MEI ≥: -.--

ErP status: EuP Standalone/Prod.

Net weight:171 kgGross weight:206 kgShipping volume:0.295 m³Country of origin:GBCustom tariff no.:84137029