

Data sheet**Hydraulic data**

Energy efficiency index (EEI)	0,19
Maximum operating pressure P_N	10 bar
Head max H_{\max}	8,0 m
Flow max hr $Q_{\max \text{ hr}}$	10,0 m ³ /h
Flow max add $Q_{\max \text{ add}}$	18,0 m ³ /h
Minimum suction head at 50 °C m	3 m
Minimum suction head at 95 °C m	10 m
Minimum suction head at 110 °C	16 m
Min. fluid temperature T_{\min}	-10 °C
Max. fluid temperature T_{\max}	110 °C
Min. ambient temperature T_{\min}	-10 °C
Max. ambient temperature T_{\max}	40 °C

Motor data

Mains connection	1~230 V ±10%, 50/60 Hz
Min. current I_{\min}	0,11 A
Max. current I_{\max}	1,1 A
Min. speed n_{\min}	750 1/min
Max. speed n_{\max}	3550 1/min
Power consumption $P_{1 \min}$	7 W
Power consumption $P_{1 \max}$	160 W
Interference emission	EN 61800-3;2004+A1;2012 /residential area (C1)
Interference immunity	EN 61800-3;2004+A1;2012 /industrial environment (C2)
Insulation class	F
Protection class	IPX4D

Materials

Pump housing	Cast iron
Impeller	PPS-GF40
Shaft	Stainless steel
Bearing	Carbon-graphite

Installation dimensions

Pipe connection on the pressure side DNd	DN 32
Pipe connection on the suction side DNs	DN 32
Port-to-port length L_0	220 mm