

Data sheet

Hydraulic data

Energy efficiency index (EEI)	0,19
Maximum operating pressure <i>PN</i>	10 bar
Head max <i>H</i>_{max}	11,0 m
Flow max hr <i>Q</i>_{max hr}	15,0 m ³ /h
Flow max add <i>Q</i>_{max add}	23,0 m ³ /h
Minimum suction head at 50 °C <i>m</i>	3 m
Minimum suction head at 95 °C <i>m</i>	10 m
Minimum suction head at 110 °C	16 m
Min. fluid temperature <i>T</i>_{min}	-10 °C
Max. fluid temperature <i>T</i>_{max}	110 °C
Min. ambient temperature <i>T</i>_{min}	-10 °C
Max. ambient temperature <i>T</i>_{max}	40 °C

Motor data

Mains connection	1~230 V ±10%, 50/60 Hz
Min. current <i>I</i>_{min}	0,11 A
Max. current <i>I</i>_{max}	1,42 A
Min. speed <i>n</i>_{min}	750 1/min
Max. speed <i>n</i>_{max}	4400 1/min
Power consumption <i>P</i>_{1 min}	7 W
Power consumption <i>P</i>_{1 max}	320 W
Interference emission	EN 61800-3;2004+A1;2012 /residential area (C1)
Interference immunity	EN 61800-3;2004+A1;2012 /industrial environment (C2)
Insulation class	F
Protection class	IPX4D

Materials

Pump housing	Cast iron
Impeller	PPS-GF40
Shaft	1.4122, DLC-coated
Bearing	Carbon, antimony-impregnated

Installation dimensions

Pipe connection on the pressure side <i>D</i>_{Nd}	DN 32
Pipe connection on the suction side <i>D</i>_{Ns}	DN 32
Port-to-port length <i>L</i>_O	220 mm