

This insulation set for Flamcovent (Smart) can be easily attached and consists of two halves that lock into each other by means of hook fasteners and deep-drawn synthetic caps. The melamine insulation foam (thickness 50 mm) is glued to the polystyrene outer jacket (thickness 1 mm).

Advantages

- Suitable for retrospective installation.
- 100% recyclable.

Technical Specifications

- Insulation value (λ): 0.035 W/mK.
- Fire class B2 according to DIN 4102.
- Colour: aluminium coloured (RAL 9006).



| | | |
|-------------|---------------------------|-----|
| Description | Flamcovent DN65 IsoPlus | |
| Order Code | 28161 | |
| GTIN | 08712874281615 | |
| Model | <u>Flamcovent IsoPlus</u> | |
| Dimensions | A [mm] | 500 |
| | B [mm] | 280 |
| Weight [kg] | 1.4 | |

Classification General Data

| | |
|----------------------|--|
| Etim Group | Filters/separators |
| Etim Class | Insulation cover for air-/dirt separator |
| Product Name | Flamcovent DN65 IsoPlus |
| Brand | Flamco |
| Product Type | 65 |
| Artikelnummer | 28161 |

Attributes

| | |
|-----------------------------------|---------------------|
| Material insulation | Other |
| Material casing | Polystyrene (PS) |
| Temperature protected till | 120 Degrees celsius |
| Height | 500 Millimetre |

Find more information online:

[Installation and operating instruction](#)

[Flamcovent IsoPlus RFA](#)

[Export catalogue](#)

[Packaging data](#)

Fort Blauwkapel 1
1358 DB, Almere - nl

T +31 (0)36 52 62 300
E info@aalberts-hfc.com
I flamcogroup.com