

This insulation set for Flamcovent (Smart) can be easily attached and consists of two halves that lock into each other by means of hook fasteners and deep-drawn synthetic caps. The melamine insulation foam (thickness 50 mm) is glued to the polystyrene outer jacket (thickness 1 mm).

### Advantages

- Suitable for retrospective installation.
- 100% recyclable.

### Technical Specifications

- Insulation value ( $\lambda$ ): 0.035 W/mK.
- Fire class B2 according to DIN 4102.
- Colour: aluminium coloured (RAL 9006).



Description	Flamcovent DN100 IsoPlus	
Order Code	28163	
GTIN	08712874281639	
Model	<u>Flamcovent IsoPlus</u>	
Dimensions	A [mm]	650
	B [mm]	380
Weight [kg]	2.3	

### Classification General Data

Etim Group	Filters/separators
Etim Class	Insulation cover for air-/dirt separator
Product Name	Flamcovent DN100 IsoPlus
Brand	Flamco
Product Type	100
Artikelnummer	28163

### Attributes

Material insulation	Other
Material casing	Polystyrene (PS)
Temperature protected till	120 Degrees celsius
Height	650 Millimetre

### Find more information online:

[Installation and operating instruction](#)

[Flamcovent IsoPlus RFA](#)

[Export catalogue](#)

[Packaging data](#)

Fort Blauwkapel 1  
1358 DB, Almere - nl

T +31 (0)36 52 62 300  
E [info@aalberts-hfc.com](mailto:info@aalberts-hfc.com)  
I [flamcogroup.com](http://flamcogroup.com)