


Position	Qty.	Description
	1	<p data-bbox="320 338 550 365">Unilift AP12.40.08.3</p> <div data-bbox="403 398 619 779" style="text-align: center;">  </div> <p data-bbox="710 770 1193 792" style="text-align: right;">Note! Product picture may differ from actual product</p> <p data-bbox="320 801 686 860">Product No.: 96001791 Submersible drainage pump type</p> <p data-bbox="320 891 874 1034">Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 3-phase totally enclosed motor in insulation class F. The pump is fitted with a suction strainer.</p> <p data-bbox="320 1070 794 1182">The impeller is a SEMI OPEN impeller for 12 mm free passage suitable for pumping groundwater, surface water, rain water and similar.</p> <p data-bbox="320 1218 853 1303">The pump has a double shaft seal and an intermediate oil chamber pre-filled with non-toxic special oil.</p> <p data-bbox="320 1339 842 1451">The pump has a riser pipe, a cooling jacket for continuous cooling of the motor by the pumped liquid and long-life deep-groove greased-for-life ball bearings.</p> <p data-bbox="320 1487 853 1662">The pump is ready for use as it is fitted with carrying handle and is supplied with a 10 m mains cable. The mains cable is of the plug type with glass sealing compound in the socket to prevent penetration of humidity into the stator windings.</p> <p data-bbox="320 1697 917 1809">Liquid: Pumped liquid: Any Newtonian liquid Liquid temperature range: 0 .. 55 °C Density: 998.2 kg/m³</p> <p data-bbox="320 1845 821 1930">Technical: Type of impeller: SEMI OPEN Maximum particle size: 12 mm</p> <p data-bbox="320 1966 885 2101">Materials: Pump housing: Stainless steel DIN W.-Nr. 1.4301 AISI 304 Impeller: Stainless steel</p>

Position	Qty.	Description
		<p>DIN W.-Nr. 1.4301 AISI 304</p> <p>Installation: Pump outlet: Rp 1 1/2 Maximum installation depth: 7 m</p> <p>Electrical data: Power input - P1: 1.2 kW Mains frequency: 50 Hz Rated voltage: 3 x 400 V Rated current: 2.1 A Cos phi - power factor: 0,87 Rated speed: 2810 rpm Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Length of cable: 10 m Type of cable plug: NONE</p> <p>Others: Net weight: 11.5 kg Gross weight: 12.5 kg</p>

Description	Value
-------------	-------

General information:

Product name:	Unilift AP12.40.08.3
Product No:	96001791
EAN number:	5700390897161

Technical:

Max flow:	5.83 l/s
Head max:	15 m
Type of impeller:	SEMI OPEN
Maximum particle size:	12 mm

Materials:

Pump housing:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
Impeller:	Stainless steel DIN W.-Nr. 1.4301 AISI 304

Installation:

Pump outlet:	Rp 1 1/2
Maximum installation depth:	7 m
Inst dry/wet:	D/S
Installation:	horizontal or vertical

Liquid:

Pumped liquid:	Any Newtonian liquid
Liquid temperature range:	0 .. 55 °C
Density:	998.2 kg/m ³

Electrical data:

Power input - P1:	1.2 kW
P2:	0.8 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 400 V
Rated current:	2.1 A
Cos phi - power factor:	0,87
Rated speed:	2810 rpm
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Motor protec:	NONE
Thermal protec:	external
Length of cable:	10 m
Type of cable plug:	NONE

Others:

Net weight:	11.5 kg
Gross weight:	12.5 kg

