








Qty.	Description
1	<p data-bbox="201 159 536 185">HYDRO MULTI-E 3 CRIE 10-5</p> <div data-bbox="245 273 541 461">  </div> <p data-bbox="592 506 1062 530" style="text-align: center;">Note! Product picture may differ from actual product</p> <p data-bbox="201 539 464 564">Product No.: 99133119</p> <p data-bbox="201 600 1372 649">GRUNDFOS Hydro Multi-E booster sets are designed for the transfer and pressure boosting of clean water in waterworks, blocks of flats, hotels, industry, hospitals, schools, etc.</p> <p data-bbox="201 658 1455 707">GRUNDFOS Hydro Multi-E booster set consists of 2 to 4 CRIE pumps coupled in parallel and mounted on a common base frame provided with all the necessary fittings.</p> <p data-bbox="201 743 1235 770">Hydro Multi-E is mounted on a common base frame made of stainless steel (DIN W.-Nr. 1.4301).</p> <p data-bbox="201 779 844 806">On the suction side are fitted a suction manifold (DIN W.-Nr.</p> <p data-bbox="201 815 432 842">1.4401 or DIN W.-Nr.</p> <p data-bbox="201 851 1062 878">1.4571) , a pressure switch mounted on a drainable valve and an isolating valve.</p> <p data-bbox="201 887 1439 936">On the discharge side of the pumps are fitted a non-return valve, an isolating valve, a pressure gauge, two pressure transmitters mounted on a drainable valve a diaphragm tank and a stainless steel discharge manifold (DIN W.-Nr.</p> <p data-bbox="201 945 432 972">1.4401 or DIN W.-Nr.</p> <p data-bbox="201 981 293 1008">1.4571).</p> <p data-bbox="201 1016 948 1043">The Hydro Multi-E is fitted with an on/off-switch for the supply voltage.</p> <p data-bbox="201 1079 1372 1106">The Hydro Multi-E is designed for maintaining a constant pressure regardless of flow changes and fluctuation.</p> <p data-bbox="201 1137 1382 1187">The internal PI-controller regulates the number of running pumps and the speed of the pumps according to the required flow.</p> <p data-bbox="201 1218 1433 1245">The system can be operated directly on the panel of any of the pumps or via Grundfos GO (available as accessory)</p> <p data-bbox="201 1308 513 1335">Besides the system features:</p> <ul data-bbox="201 1344 845 1572" style="list-style-type: none"> 2 Digital outputs 2 Digital inputs (one used for dry run protection) 2 Analogue inputs (one used for discharge pressure sensor) Multi-Master functionality 2 Limit functions Set-point influence function Pipe filling function High efficient PM motors <p data-bbox="201 1603 584 1630">Available communication protocols:</p> <ul data-bbox="201 1639 402 1899" style="list-style-type: none"> •LON •Profibus •Modbus •SMS/GSM/GPRS •GRM •BACnet •BACnet IP •Modbus TCP •PROFINET <p data-bbox="201 1935 1279 1962">When delivered, the GRUNDFOS Hydro Multi-E booster set is factory tested and ready for operation.</p> <p data-bbox="201 2024 632 2078">Liquid: Pumped liquid: Water</p>

Qty.	Description
1	<p>Liquid temperature range: 5 .. 60 °C Selected liquid temperature: 20 °C Density: 998.2 kg/m³</p> <p>Technical: Max flow: 54 m³/h</p> <p>Materials: Pump housing: Stainless steel</p> <p>Installation: Maximum operating pressure: 10 bar Maximum permissible inlet pressure: PN 10 bar Flange standard: DIN2642 Manifold inlet: DN 80 Manifold outlet: DN 80</p> <p>Electrical data: IE Efficiency class: IE5 Power (P2) main pump: 3 kW Mains frequency: 50 / 60 Hz Rated voltage: 3 x 380-415 V Rated current: 17 A Start. method: electronically Enclosure class (IEC 34-5): IP54</p> <p>Tank: Volume of pressure tank: 12 l Diaphragm tank: Yes</p> <p>Others: Net weight: 242 kg Gross weight: 308 kg Shipping volume: 1.04 m³ Language: GB Danish VVS No.: 385552605 Country of origin: GB Custom tariff no.: 84137075</p>



99133119 HYDRO MULTI-E 3 CRIE 10-5





Description	Value
General information:	
Product name:	HYDRO MULTI-E 3 CRIE 10-5
Product No:	99133119
EAN number:	5712607360337
Technical:	
Max flow:	54 m ³ /h
Min flow system:	4.8 m ³ /h
Head max:	74 m
Pump name:	CRIE 10-5
Number of pumps:	3
Materials:	
Pump housing:	Stainless steel
Manifolds:	Stainless steel
Installation:	
Maximum operating pressure:	10 bar
Maximum permissible inlet pressure:	PN 10 bar
Flange standard:	
Manifold inlet:	DIN2642
Manifold outlet:	DN 80
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	5 .. 60 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m ³
Electrical data:	
IE Efficiency class:	IE5
Power (P2) main pump:	3 kW
Mains frequency:	50 / 60 Hz
Rated voltage:	3 x 380-415 V
Rated current:	17 A
Start. method:	electronically
Enclosure class (IEC 34-5):	IP54
Tank:	
Volume of pressure tank:	12 l
Diaphragm tank:	Yes
Others:	
Net weight:	242 kg
Gross weight:	308 kg
Shipping volume:	1.04 m ³
Language:	GB
Danish VVS No.:	385552605
Country of origin:	GB
Custom tariff no.:	84137075



99133119 HYDRO MULTI-E 3 CRIE 10-5




99133119 HYDRO MULTI-E 3 CRIE 10-5



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

99133119 HYDRO MULTI-E 3 CRIE 10-5



Note! All units are in [mm] unless others are stated.

